


Features

- Low Frequency Power Amplifier Application
- Power Switching Applications



Maximum Ratings (Ta=25°C unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	-35	V
V_{CEO}	Collector-Emitter Voltage	-30	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_C	Collector Current	-800	mA
P_C	Collector Power Dissipation	200	mW
$R_{\theta JA}$	Thermal Resistance From Junction To Ambient	625	°C/W
T_J, T_{stg}	Operation Junction and Storage Temperature Range	-55~+150	°C

Ordering Information (Example)



Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
2SA1298	SOT-23	IO/IY	3,000	45,000	180,000	7"reel







Electrical Characteristics (Ta=25°C unless otherwise specified)

Symbol	Parameter	Condition	Min	Typ	Max	Unit
$V_{(BR)CBO}$	Collector-base breakdown voltage	$I_C = -1\text{mA}$, $I_E = 0$	-35	--	--	V
$V_{(BR)CEO}$	Collector-emitter breakdown voltage	$I_C = -10\text{mA}$, $I_B = 0$	-30	--	--	V
$V_{(BR)EBO}$	Emitter-base breakdown voltage	$I_E = -1\text{mA}$, $I_C = 0$	-5	--	--	V
I_{CBO}	Collector cut-off current	$V_{CB} = -30\text{V}$, $I_E = 0$	--	--	-0.1	μA
I_{EBO}	Emitter cut-off current	$V_{EB} = -5\text{V}$, $I_C = 0$	--	--	-0.1	μA
$H_{FE(1)}$	DC current gain	$V_{CE} = -1\text{V}$, $I_C = -100\text{mA}$	100	--	320	
$H_{FE(2)}$	DC current gain	$V_{CE} = -1\text{V}$, $I_C = -800\text{mA}$	40	--	--	
$V_{CE(sat)}$	Collector-emitter saturation voltage	$I_C = -500\text{mA}$, $I_B = -20\text{mA}$	--	--	-0.4	V
V_{BE}	Base-emitter voltage	$V_{CE} = -1\text{V}$, $I_C = -10\text{mA}$	-0.5	--	-0.8	V
C_{ob}	Collector output capacitance	$V_{CB} = -10\text{V}$, $I_E = 0$, $f = 1\text{MHz}$	--	13	--	pF
f_T	Transition frequency	$V_{CE} = -5\text{V}$, $I_C = -10\text{mA}$	--	120	--	MHz


Classification of hFE

Rank	O	Y
Marking	IO	IY
Range	100-200	160-320

Typical Operating Characteristics




SOT-23 Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E1	2.250	2.550	0.088	0.100
E	1.200	1.400	0.047	0.055
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°