



Features


- High DC Current gain.
- Complimentary to 2SB624



SOT-23 top view



Schematic diagram



Marking and pin assignment



Halogen-Free

Maximum Ratings (Ta=25°C unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	30	V
V_{CEO}	Collector-Emitter Voltage	25	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current	700	mA
P_C	Collector Power Dissipation	200	mW
$R_{\theta JA}$	Thermal Resistance From Junction To Ambient	625	°C/W
T_J, T_{stg}	Operation Junction and Storage Temperature Range	-55~+150	°C

Ordering Information (Example)



Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
2SD596	SOT-23	DV1/DV2/DV3/DV4/DV5	3,000	45,000	180,000	7"reel







Electrical Characteristics (Ta=25°C unless otherwise specified)

Symbol	Parameter	Condition	Min	Typ	Max	Unit
$V_{(BR)CBO}$	Collector-base breakdown voltage	$I_C=100\mu A, I_E=0$	30	--	--	V
$V_{(BR)CEO}$	Collector-emitter breakdown voltage	$I_C=1mA, I_B=0$	25	--	--	V
$V_{(BR)EBO}$	Emitter-base breakdown voltage	$I_E=100\mu A, I_C=0$	5	--	--	V
I_{CBO}	Collector cut-off current	$V_{CB}=30V, I_E=0$	--	--	0.1	μA
I_{EBO}	Emitter cut-off current	$V_{EB}=5V, I_C=0$	--	--	0.1	μA
$H_{FE(1)}^*$	DC current gain	$V_{CE}=1V, I_C=100mA$	110	--	400	
$H_{FE(2)}^*$	DC current gain	$V_{CE}=1V, I_C=700mA$	50	--	--	
$V_{CE(sat)}^*$	Collector-emitter saturation voltage	$I_C=700mA, I_B=10mA$	--	--	0.6	V
V_{BE}^*	Base-emitter voltage	$V_{CE}=6V, I_C=10mA$	0.6	--	0.7	V
C_{ob}	Collector output capacitance	$V_{CB}=6V, I_E=0, f=10MHz$	--	12	--	pF
f_T	Transition frequency	$V_{CE}=6V, I_C=10mA$	170	--	--	MHz


Classification of hFE

Rank	DV1	DV2	DV3	DV4	DV5
Marking	DV1	DV2	DV3	DV4	DV5
Range	110-180	135-220	170-370	200-320	250-400

Typical Operating Characteristics




SOT-23 Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E1	2.250	2.550	0.088	0.100
E	1.200	1.400	0.047	0.055
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°