

Features


- Trench Power LV MOSFET technology
- High Density Cell Design for Low $R_{DS(ON)}$
- High Speed switching

Application

- Battery protection
- Load switch
- Power management



Product Summary

V_{DS}	$R_{DS(ON)}$ TYP	I_D
600V	310 Ω @10V	0.021A
	330 Ω @4.5V	



B127: Device code

Marking and pin assignment



Halogen-Free

Absolute Maximum Ratings (TA=25°C unless otherwise noted)

Symbol	Parameter	Rating	Unit
Common Ratings (TC=25°C Unless Otherwise Noted)			
V_{DS}	Drain-Source Breakdown Voltage	600	V
V_{GS}	Gate-Source Voltage	± 20	V
T_J	Maximum Junction Temperature	150	°C
T_{STG}	Storage Temperature Range	-55 to 150	°C
I_S	Diode Continuous Forward Current	$T_C=25^\circ\text{C}$ 0.021	A

Mounted on Large Heat Sink

I_{DM}	Pulse Drain Current Tested	$T_C=25^\circ\text{C}$ 0.09	A
I_D	Continuous Drain Current	$T_C=25^\circ\text{C}$ 0.021	A
P_D	Maximum Power Dissipation	$T_C=25^\circ\text{C}$ 0.5	W
$R_{\theta JA}$	Thermal Resistance Junction-Ambient	135	°C/W

Ordering Information (Example)

Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
BSS127	SOT-23	B127	3,000	45,000	180,000	7" reel

Electrical Characteristics (TJ=25℃ unless otherwise noted)						
Symbol	Parameter	Condition	Min	Typ	Max	Unit
Static Electrical Characteristics @ TJ = 25℃ (unless otherwise stated)						
BV _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	600	--	--	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =600V, V _{GS} =0V	--	--	0.1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V, V _{DS} =0V	--	--	±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =8μA	1.4	--	2.6	V
R _{DS(on)}	Drain-Source On-State Resistance	V _{GS} =10V, I _D =16mA	--	310	500	Ω
		V _{GS} =4.5V, I _D =16mA	--	330	600	Ω
Dynamic Electrical Characteristics @ TJ = 25℃ (unless otherwise stated)						
C _{ISS}	Input Capacitance	V _{DS} =25V, V _{GS} =0V, f=1MHz	--	21	--	pF
C _{OSS}	Output Capacitance		--	2.4	--	pF
C _{RSS}	Reverse Transfer Capacitance		--	1	--	pF
Switching Characteristics						
Q _g	Total Gate Charge	V _{DD} =300V, I _D =0.01A, V _{GS} =0 to 10V	--	0.07	--	nC
Q _{gs}	Gate Source Charge		--	0.31	--	nC
Q _{gd}	Gate Drain Charge		--	0.65	--	nC
t _{d(on)}	Turn-on Delay Time	V _{DD} =300V, I _D =0.01A, V _{GS} =10V, R _G =6Ω	--	6.1	--	nS
t _r	Turn-on Rise Time		--	9.7	--	nS
t _{d(off)}	Turn-Off Delay Time		--	14	--	nS
t _f	Turn-Off Fall Time		--	114	--	nS
Source- Drain Diode Characteristics						
V _{SD}	Forward on voltage	Tj=25℃, Is=0.016A	--	--	1.2	V

Typical Operating Characteristics




Fig1. Typical Output Characteristics




Fig2. Typical Gate Charge Vs. Gate-Source Voltage




Fig3. Normalized On-Resistance Vs. Temperature




Fig4. On-Resistance Vs. Drain-Source Current




Fig5. Maximum Safe Operating Area





Fig6 Typical Capacitance Vs. Drain-Source Voltage

SOT-23 Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E1	2.250	2.550	0.088	0.100
E	1.200	1.400	0.047	0.055
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°