

Features


- Excellent h_{FE} Linearity
- Complementary to KTC4076

Applications


- General Purpose Switching



SOT-323 top view



Schematic diagram



Marking and pin assignment

X:Rank



Halogen-Free

Maximum Ratings (Ta=25°C unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	-35	V
V_{CEO}	Collector-Emitter Voltage	-30	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_C	Collector Current	-500	mA
P_C	Collector Power Dissipation	100	mW
$R_{\theta JA}$	Thermal Resistance From Junction To Ambient	1250	°C/W
T_J, T_{stg}	Operation Junction and Storage Temperature Range	-55~+150	°C

Ordering Information (Example)

Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
KTA2015	SOT-323	ZY/ZO	3,000	45,000	180,000	7"reel




Electrical Characteristics (Ta=25°C unless otherwise specified)

Symbol	Parameter	Condition	Min	Typ	Max	Unit
$V_{(BR)CBO}$	Collector-base breakdown voltage	$I_C=-100\mu A, I_E=0$	-35	--	--	V
$V_{(BR)CEO}$	Collector-emitter breakdown voltage	$I_C=-1mA, I_B=0$	-30	--	--	V
$V_{(BR)EBO}$	Emitter-base breakdown voltage	$I_E=-100\mu A, I_C=0$	-5	--	--	V
I_{CBO}	Collector cut-off current	$V_{CB}=-35V, I_E=0$	--	--	-0.1	μA
I_{EBO}	Emitter cut-off current	$V_{EB}=-5V, I_C=0$	--	--	-0.1	μA
h_{FE1}	DC current gain	$V_{CE}=-1V, I_C=-100mA$	70	--	240	
h_{FE2}	DC current gain	$V_{CE}=-6V, I_C=-400mA$	25	--	--	
$V_{CE(sat)}$	Collector-emitter saturation voltage	$I_C=-100mA, I_B=-10mA$	--	--	-0.25	V
V_{BE}	Base-emitter voltage	$I_C=-1V, I_C=-100mA$	--	--	-1	V
f_T	Transition frequency	$V_{CB}=-6V, I_C=20mA$	--	200	--	MHz
C_{ob}	Collector output capacitance	$V_{CB}=-6V, I_E=0, f=1MHz$	--	13	--	pF

Classification of hFE

Rank	O(2)	Y(4)	O	Y
Marking	ZO	ZY	ZO	ZY
Rang $h_{FE}(1)$	70-140	120-240		
$h_{FE}(1)$			25Min	40Min

SOT-323 Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.200	0.400	0.008	0.016
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650TYP		0.026TYP	
e1	1.200	1.400	0.047	0.055
L	0.525REF		0.021REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°