

Features


- High density cell design for ultra low $R_{DS(ON)}$
- Fully characterized avalanche voltage and current
- Good stability and uniformity with high EAS

Product Summary


V_{DS}	$R_{DS(ON)}$ TYP	I_D
-30V	8.5mΩ@-10V	-50A
	11.7mΩ@-4.5V	

Application


- Battery and loading switching
- Excellent package for good heat dissipation



PDFN5X6-8L view



Schematic diagram



Marking and pin assignment

MC0D50AP: Device code
XXXX : Code



Halogen-Free

Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Rating	Unit
--------	-----------	--------	------

Common Ratings ($T_C=25^{\circ}\text{C}$ Unless Otherwise Noted)

V_{DS}	Drain-Source Breakdown Voltage	-30	V
V_{GS}	Gate-Source Voltage	± 20	V
E_{AS}	Single pulse avalanche energy	77	mJ
T_J, T_{STG}	Storage Temperature Range	-55 to 175	$^{\circ}\text{C}$
I_S	Diode Continuous Forward Current	$T_C=25^{\circ}\text{C}$ -50	A

Mounted on Large Heat Sink

I_{DM}	Pulse Drain Current Tested	$T_C=25^{\circ}\text{C}$ -210	A
I_D	Continuous Drain Current	$T_C=25^{\circ}\text{C}$ -50	A
P_D	Maximum Power Dissipation	$T_C=25^{\circ}\text{C}$ 65	W
$R_{\theta JA}$	Thermal Resistance Junction-Ambient	62.5	$^{\circ}\text{C/W}$

Ordering Information (Example)

Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MC0D50AP	PDFN5X6-8L	MC0D50AP	5,000	10,000	70,000	13"reel

Electrical Characteristics (TJ=25℃ unless otherwise noted)						
Symbol	Parameter	Condition	Min	Typ	Max	Unit
Static Electrical Characteristics @ TJ = 25℃ (unless otherwise stated)						
BV _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =-250μA	-30	--	--	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-30V, V _{GS} =0V	--	--	-1.0	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V, V _{DS} =0V	--	--	±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250μA	-1.0	-1.5	-2.5	V
R _{DS(on)}	Drain-Source On-State Resistance	V _{GS} =-10V, I _D =-25A	--	8.5	10	mΩ
		V _{GS} =-4.5V, I _D =-10A	--	11.7	14	mΩ
Dynamic Electrical Characteristics @ TJ = 25℃ (unless otherwise stated)						
C _{ISS}	Input Capacitance	V _{DS} =-15V, V _{GS} =0V, f=1MHz	--	1988	--	pF
C _{OSS}	Output Capacitance		--	305	--	pF
C _{RSS}	Reverse Transfer Capacitance		--	266	--	pF
Switching Characteristics						
Q _g	Total Gate Charge	V _{DD} =-15V, I _D =-25A, V _{GS} =-10V	--	35	--	nC
Q _{gs}	Gate Source Charge		--	5.8	--	nC
Q _{gd}	Gate Drain Charge		--	8.8	--	nC
t _{d(on)}	Turn-on Delay Time	V _{DD} =-15V, I _D =-25A, V _{GS} =-10V, R _G =2.5Ω	--	11	--	nS
t _r	Turn-on Rise Time		--	7.7	--	nS
t _{d(off)}	Turn-Off Delay Time		--	43.3	--	nS
t _f	Turn-Off Fall Time		--	18	--	nS
Source- Drain Diode Characteristics						
V _{SD}	Forward on voltage	Tj=25℃, Is=-25A	--	--	-1.2	V

Typical Operating Characteristics




Fig1. Typical Output Characteristics




Fig2. Typical Gate Charge Vs. Gate-Source Voltage




Fig3. Normalized On-Resistance Vs. Temperature




Fig4. On-Resistance Vs. Drain-Source Current




Fig5. Maximum Safe Operating Area





Fig6 Typical Capacitance Vs. Drain-Source Voltage

PDFN5X6-8L Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	0.950	1.050	0.035	0.039
A3	0.254REF.		0.010REF.	
D	4.950	5.050	0.196	0.200
E	5.950	6.050	0.235	0.239
D1	4.026	4.126	0.159	0.163
E1	3.510	3.610	0.139	0.143
D2	4.850	4.950	0.192	0.196
E2	5.700	5.800	0.225	0.229
k	1.190	1.390	0.047	0.055
b	0.300	0.400	0.012	0.016
e	1.270TYP.		0.050TYP.	
L	0.559	0.711	0.022	0.028
L1	0.424	0.576	0.017	0.023
H	0.574	0.726	0.023	0.029
θ	10°	12°	10°	12°