


Features

- High Speed Power Switching, Logic level
- Enhanced Body diode DV/DT capability
- Enhanced Avalanche Ruggedness
- 100% UIS Tested, 100% Rg Tested
- Lead Free, Halogen Free

Application

- DC/DC Converter
- Motor Drivers
- Ideal for high-frequency switching and synchronous rectification




MC0E240AG: Device code
XXXX: Code


Marking and pin assignment

Product Summary

V_{DS}	$R_{DS(ON)}$ TYP	I_D
40V	1.15m Ω @10V	240A
	1.65m Ω @4.5V	



PDFN5X6-8L



Schematic diagram



Halogen-Free

Absolute Maximum Ratings (TA=25°C unless otherwise noted)

Symbol	Parameter	Rating	Unit
--------	-----------	--------	------

Common Ratings (TC=25°C Unless Otherwise Noted)

V _{DS}	Drain-Source Breakdown Voltage		40	V
V _{GS}	Gate-Source Voltage		±20	V
E _{AS}	Single pulse avalanche energy		676	mJ
T _J , T _{STG}	Storage Temperature Range		-55 to 150	°C
I _S	Diode Continuous Forward Current	Tc=25°C	240	A

Mounted on Large Heat Sink







I_{DM}	Pulse Drain Current Tested	$T_C=25^\circ\text{C}$	880	A
I_D	Continuous Drain Current	$T_C=25^\circ\text{C}$	240	A
P_D	Maximum Power Dissipation	$T_C=25^\circ\text{C}$	100	W
$R_{\theta JA}$	Thermal Resistance Junction-Ambient		55	°C/W


Ordering Information (Example)

Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MC0E240AG	PDFN5X6-8L	MC0E240AG	5,000	10,000	70,000	13"reel

Electrical Characteristics (TJ=25°C unless otherwise noted)						
Symbol	Parameter	Condition	Min	Typ	Max	Unit
Static Electrical Characteristics @ TJ = 25°C (unless otherwise stated)						
BV _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	40	–	–	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =40V, V _{GS} =0V	–	–	1.0	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V, V _{DS} =0V	–	–	±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	1.0	1.8	2.5	V
R _{DS(on)}	Drain-Source On-State Resistance	V _{GS} =10V, I _D =30A	–	1.15	1.5	mΩ
		V _{GS} =4.5V, I _D =20A	–	1.65	2.2	mΩ
Dynamic Electrical Characteristics @ TJ = 25°C (unless otherwise stated)						
C _{ISS}	Input Capacitance	V _{DS} =20V, V _{GS} =0V, f=500KHz	–	4380	–	pF
C _{OSS}	Output Capacitance		–	1490	–	pF
C _{RSS}	Reverse Transfer Capacitance		–	30	–	pF
Switching Characteristics						
Q _g	Total Gate Charge	V _{DS} =20V, I _D =55A, V _{GS} =10V	–	56	–	nC
Q _{gs}	Gate Source Charge		–	27	–	nC
Q _{gd}	Gate Drain Charge		–	5.6	–	nC
t _{d(on)}	Turn-on Delay Time	V _{DD} =20V, I _D =55A, V _{GS} =10V, R _G =3Ω	–	22	–	nS
t _r	Turn-on Rise Time		–	8.5	–	nS
t _{d(off)}	Turn-Off Delay Time		–	44	–	nS
t _f	Turn-Off Fall Time		–	51.8	–	nS
Source- Drain Diode Characteristics						
V _{SD}	Forward on voltage	Tj=25°C, Is=30A,	–	0.9	1.2	V

Typical Operating Characteristics





Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	0.950	1.050	0.035	0.039
A3	0.254REF.		0.010REF.	
D	4.950	5.050	0.196	0.200
E	5.950	6.050	0.235	0.239
D1	4.026	4.126	0.159	0.163
E1	3.510	3.610	0.139	0.143
D2	4.850	4.950	0.192	0.196
E2	5.700	5.800	0.225	0.229
k	1.190	1.390	0.047	0.055
b	0.300	0.400	0.012	0.016
e	1.270TYP.		0.050TYP.	
L	0.559	0.711	0.022	0.028
L1	0.424	0.576	0.017	0.023
H	0.574	0.726	0.023	0.029
θ	10°	12°	10°	12°