


Features


- Low Saturation Voltage
- High Speed Switching



SOT-89-3L top view



Schematic diagram



Marking and pin assignment



Halogen-Free

Maximum Ratings (Ta=25°C unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	-100	V
V_{CEO}	Collector-Emitter Voltage	-60	V
V_{EBO}	Emitter-Base Voltage	-7	V
I_C	Collector Current	-6	A
$P_D^{①}$	Power Dissipation	1.5	W
$R_{\theta JA}^{①}$	Thermal Resistance From Junction To Ambient	83.3	°C/W
T_J, T_{stg}	Operation Junction and Storage Temperature Range	-55~+150	°C



Ordering Information (Example)






Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MLSA606PL	SOT-89-3L	606PL	1,000	10,000	40,000	7"reel



Electrical Characteristics (Ta=25°C unless otherwise specified)

Symbol	Parameter	Condition	Min	Typ	Max	Unit
$V_{(BR)CBO}$	Collector-base breakdown voltage	$I_C = -0.1mA, I_E = 0$	-100	--	--	V
$V_{(BR)CEO}$	Collector-emitter breakdown voltage	$I_C = -10mA, I_B = 0$	-60	--	--	V
$V_{(BR)EBO}$	Emitter-base breakdown voltage	$I_E = -0.1mA, I_C = 0$	-7	--	--	V
I_{CBO}	Collector cut-off current	$V_{CB} = -80V, I_E = 0$	--	--	-20	nA
I_{EBO}	Emitter cut-off current	$V_{EB} = -6V, I_C = 0$	--	--	-10	nA
h_{FE}	DC current gain	$V_{CE} = -1V, I_C = -10mA$	100	--	--	--
		$V_{CE} = -1V, I_C = -2A$	100	--	300	
		$V_{CE} = -1V, I_C = -5A$	45	--	--	
		$V_{CE} = 1V, I_C = -10A$	10	--	--	
$V_{CE(sat)}$	Collector-emitter saturation voltage	$I_C = -100mA, I_B = -10mA$	--	--	-20	mV
		$I_C = -1A, I_B = -100mA$	--	--	-65	
		$I_C = -2A, I_B = -200mA$	--	--	-150	
		$I_C = -5A, I_B = -500mA$	--	--	-280	
$V_{BE(sat)}$	Base-emitter saturation voltage	$I_C = -5A, I_B = -500mA$	--	--	-1.15	V
$V_{BE(on)}$	Base-emitter on voltage	$I_C = -5A, V_{CE} = -1V$	--	--	-1	V
C_{ob}	Collector output capacitance	$V_{CB} = -10V, I_E = 0, f = 1MHz$	--	65	--	pF
f_T	Transition frequency	$V_{CE} = -10V, I_C = -0.1A, f = 100MHz$	30	--	--	MHz


Notes: 1. Device mounted on 1 in2 FR-4 board with 2oz. single-sided Copper,
in a still air environment with TA=25 °C

Typical Characteristics






SOT-89-3L Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions in Inches	
	Min	Max	Min	Max
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.020
b1	0.400	0.580	0.016	0.023
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.550 REF		0.061 REF	
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500 TYP		0.060 TYP	
e1	3.000 TYP		0.118 TYP	
L	0.900	1.200	0.035	0.047