

Features


- High density cell design for ultra low $R_{DS(ON)}$
- Fully characterized avalanche voltage and current
- Excellent package for good heat dissipation

Product Summary

V_{DS}	$R_{DS(ON)}$ MAX	I_D MAX
30V	15mΩ@10V	8A
	20mΩ@4.5V	


Application

- Power switching application




3008A: Device code

Marking and pin assignment



SOT-23-3L top view



Schematic diagram



Pb-Free



Halogen-Free

Absolute Maximum Ratings (TA=25°C unless otherwise noted)

Symbol	Parameter	Rating	Unit
--------	-----------	--------	------

Common Ratings (TC=25°C Unless Otherwise Noted)

V_{DS}	Drain-Source Breakdown Voltage	30	V
V_{GS}	Gate-Source Voltage	±20	V
T_J	Maximum Junction Temperature	150	°C
T_{STG}	Storage Temperature Range	-50 to 155	°C
I_S	Diode Continuous Forward Current	$T_c=25^\circ\text{C}$ 8	A

Mounted on Large Heat Sink







I_{DM}	Pulse Drain Current Tested	$T_c=25^\circ\text{C}$ 32	A
I_D	Continuous Drain Current	$T_c=25^\circ\text{C}$ 8	A
P_D	Maximum Power Dissipation	$T_c=25^\circ\text{C}$ 1.1	W
$R_{\theta JA}$	Thermal Resistance Junction-Ambient	135	°C/W

Ordering Information (Example)




Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MLSK3008A	SOT-23-3L	3008A	3,000	45,000	180,000	7" reel

Electrical Characteristics (TJ=25°C unless otherwise noted)						
Symbol	Parameter	Condition	Min	Typ	Max	Unit
Static Electrical Characteristics @ TJ = 25°C (unless otherwise stated)						
BV _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	30	–	–	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =30V, V _{GS} =0V	–	–	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V, V _{DS} =0V	–	–	±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	1.0	1.5	2.5	V
R _{DS(on)}	Drain-Source On-State Resistance	V _{GS} =10V, I _D =6A	–	10	15	mΩ
		V _{GS} =4.5V, I _D =4A	–	15	20	mΩ
Dynamic Electrical Characteristics @ TJ = 25°C (unless otherwise stated)						
CISS	Input Capacitance	V _{DS} =15V, V _{GS} =0V, f=1MHz	–	1055	–	pF
COSS	Output Capacitance		–	180	–	pF
CRSS	Reverse Transfer Capacitance		–	130	–	pF
Switching Characteristics						
Qg	Total Gate Charge	V _{DS} =15V, I _D =6A, V _{GS} =10V	–	25	–	nC
Qgs	Gate Source Charge		–	3.5	–	nC
Qgd	Gate Drain Charge		–	6	–	nC
td(on)	Turn-on Delay Time	V _{DS} =15V, R _L =1.8Ω, V _{GS} =10V, R _G =3Ω	–	5	–	nS
tr	Turn-on Rise Time		–	12	–	nS
td(off)	Turn-Off Delay Time		–	19	–	nS
tf	Turn-Off Fall Time		–	6	–	nS
Source- Drain Diode Characteristics						
VSD	Forward on voltage	Tj=25°C, Is=8A	–	–	1.2	V

Typical Operating Characteristics



SOT-23-3L Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.042	0.050
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.042	0.046
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.112	0.120
E	1.500	1.700	0.060	0.068
E1	2.650	2.950	0.106	0.118
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°