

Features

- Trench Power LV MOSFET technology
- High Power and Current handling capability
- Low Gate Charge

Product Summary


V_{DS}	$R_{DS(ON)}$ TYP	I_D
30V	4.5mΩ@10V	14A
	7.5mΩ@4.5V	

Application


- PWM applications
- Power management
- Load switch



SOT-23-3L top view



Schematic diagram



3014A: Device code

Marking and pin assignment



Halogen-Free

Absolute Maximum Ratings (TA=25°C unless otherwise noted)

Symbol	Parameter	Rating	Unit
--------	-----------	--------	------

Common Ratings (TC=25°C Unless Otherwise Noted)

V _{DS}	Drain-Source Breakdown Voltage		30	V
V _{GS}	Gate-Source Voltage		±20	V
T _J	Maximum Junction Temperature		150	°C
T _{STG}	Storage Temperature Range		-55 to 150	°C
I _S	Diode Continuous Forward Current	Tc=25°C	14	A

Mounted on Large Heat Sink

I_{DM}	Pulse Drain Current Tested	$T_C=25^{\circ}C$	70	A
I_D	Continuous Drain Current	$T_C=25^{\circ}C$	14	A
P_D	Maximum Power Dissipation	$T_C=25^{\circ}C$	1.2	W
$R_{\theta JA}$	Thermal Resistance Junction-to-Ambient		108	°C/W







Ordering Information (Example)

Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MLSK3014A	SOT-23-3L	3014A	3,000	45,000	180,000	7"reel




Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Condition	Min	Typ	Max	Unit
Static Electrical Characteristics @ TJ = 25°C (unless otherwise stated)						
BV _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	30	--	--	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =30V, V _{GS} =0V	--	--	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V, V _{DS} =0V	--	--	±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	1.0	1.5	2.5	V
R _{DS(on)}	Drain-Source On-State Resistance	V _{GS} =10V, I _D =10A	--	4.5	6	mΩ
		V _{GS} =4.5V, I _D =6A	--	7.5	10	mΩ
Dynamic Electrical Characteristics @ TJ = 25°C (unless otherwise stated)						
C _{ISS}	Input Capacitance	V _{DS} =15V, V _{GS} =0V, f=1MHz	--	1050	--	pF
C _{OSS}	Output Capacitance		--	220	--	pF
C _{RSS}	Reverse Transfer Capacitance		--	190	--	pF
Switching Characteristics						
Q _g	Total Gate Charge	V _{DS} =15V, I _D =16A, V _{GS} =10V	--	33	--	nC
Q _{gs}	Gate Source Charge		--	7	--	nC
Q _{gd}	Gate Drain Charge		--	11	--	nC
t _{d(on)}	Turn-on Delay Time	V _{DD} =15V, I _D =16A, V _{GS} =10V, R _G =2.5Ω	--	5	--	nS
t _r	Turn-on Rise Time		--	43	--	nS
t _{d(off)}	Turn-Off Delay Time		--	23	--	nS
t _f	Turn-Off Fall Time		--	3	--	nS
Source- Drain Diode Characteristics						
V _{SD}	Forward on voltage	T _J =25°C, I _S =10A	--	--	1.2	V

Typical Operating Characteristics



SOT-23-3L Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.042	0.050
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.042	0.046
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.112	0.120
E	1.500	1.700	0.060	0.068
E1	2.650	2.950	0.106	0.118
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
theta	0°	8°	0°	8°