

Features



- Leading trench technology for low $R_{DS(on)}$
- Low Gate Charge

Product Summary

V_{DS}	$R_{DS(on)}$ TYP	I_D
-20V	90mΩ@-4.5V	-3A
	120mΩ@-2.5V	

Application

- Video monitor
- Power management



Halogen-Free

Absolute Maximum Ratings (TA=25°C unless otherwise noted)

Symbol	Parameter	Rating	Unit
--------	-----------	--------	------

Common Ratings (TC=25°C Unless Otherwise Noted)

V_{DS}	Drain-Source Breakdown Voltage	-20	V
V_{GS}	Gate-Source Voltage	±8	V
T_J	Maximum Junction Temperature	150	°C
T_{STG}	Storage Temperature Range	-55 to 150	°C
I_S	Diode Continuous Forward Current	$T_C=25^{\circ}C$ -3	A

Mounted on Large Heat Sink







I_{DM}	Pulse Drain Current Tested	$T_C=25^{\circ}C$ -12	A
I_D	Continuous Drain Current	$T_C=25^{\circ}C$ -3	A
P_D	Maximum Power Dissipation	$T_C=25^{\circ}C$ 1.2	W
$R_{\theta JA}$	Thermal Resistance Junction-to-Ambient	178	°C/W

Ordering Information (Example)


Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MLSMGC03	DFN2X2-6L	GC03	3,000	45,000	180,000	7"reel

Electrical Characteristics (T _J =25 °C unless otherwise noted)						
Symbol	Parameter	Condition	Min	Typ	Max	Unit
Static Electrical Characteristics @ T _J = 25°C (unless otherwise stated)						
BV _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =-250μA	-20	--	--	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-20V, V _{GS} =0V	--	--	-1.0	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±8V, V _{DS} =0V	--	--	±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250μA	-0.45	-0.62	-1.0	V
R _{DS(on)}	Drain-Source On-State Resistance	V _{GS} =-4.5V, I _D =-3A	--	90	120	mΩ
		V _{GS} =-2.5V, I _D =-1.5A	--	120	160	mΩ
Dynamic Electrical Characteristics @ T _J = 25°C (unless otherwise stated)						
C _{ISS}	Input Capacitance	V _{DS} =-10V, V _{GS} =0V, f=1MHz	--	248	--	pF
C _{OSS}	Output Capacitance		--	42	--	pF
C _{RSS}	Reverse Transfer Capacitance		--	31	--	pF
Switching Characteristics						
Q _g	Total Gate Charge	V _{DS} =-10V, I _D =-3A, V _{GS} =-4.5V	--	2.9	--	nC
Q _{gs}	Gate Source Charge		--	0.45	--	nC
Q _{gd}	Gate Drain Charge		--	0.75	--	nC
t _{d(on)}	Turn-on Delay Time	V _{DD} =-10V, R _L =5Ω, V _{GS} =-4.5V, R _G =3Ω	--	9.8	--	nS
t _r	Turn-on Rise Time		--	4.9	--	nS
t _{d(off)}	Turn-Off Delay Time		--	20.5	--	nS
t _f	Turn-Off Fall Time		--	7	--	nS
Source- Drain Diode Characteristics						
V _{SD}	Forward on voltage	T _J =25°C, I _S =-3A	--	--	-1.2	V

Typical Operating Characteristics



DFN2X2-6L Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	0.600	0.700	0.024	0.027
A1	0.000	0.050	0.000	0.001
A3	0.203REF		0.007REF	
b	0.230	0.330	0.009	0.012
D	1.924	2.076	0.075	0.081
E	1.924	2.076	0.075	0.081
e	0.650TYP		0.025TYP	
L	0.224	0.376	0.008	0.014
k	0.200	-	0.007	-
E1	0.520	0.720	0.020	0.028
D1	0.800	1.000	0.031	0.039
K1	0.320TYP		0.012TYP	