

Features

- Leading trench technology for low $R_{DS(on)}$
- Low Gate Charge
- Excellent package for good heat dissipation

Product Summary

V_{DS}	$R_{DS(on)}$ MAX	I_D MAX
-60V	180mΩ@-10V	-3A
	250mΩ@-4.5V	


Application

- Video monitor
- Power management




0G03AP: Device code
 XXXX: Code

Marking and pin assignment



SOT-223 top view



Schematic diagram



Pb-Free



RoHS



Halogen-Free

Absolute Maximum Ratings (TA=25°C unless otherwise noted)

Symbol	Parameter	Rating	Unit
--------	-----------	--------	------

Common Ratings (TC=25°C Unless Otherwise Noted)

V_{DS}	Drain-Source Breakdown Voltage	-60	V
V_{GS}	Gate-Source Voltage	±20	V
T_J	Maximum Junction Temperature	150	°C
T_{STG}	Storage Temperature Range	-55 to 150	°C
I_S	Diode Continuous Forward Current	$T_c=25^\circ\text{C}$ -3	A

Mounted on Large Heat Sink

I_{DM}	Pulse Drain Current Tested	$T_c=25^\circ\text{C}$ -8	A
I_D	Continuous Drain Current	$T_c=25^\circ\text{C}$ -3	A
P_D	Maximum Power Dissipation	$T_c=25^\circ\text{C}$ 0.35	W
$R_{\theta JA}$	Thermal Resistance Junction-to-Ambient	357	°C/W

Ordering Information (Example)

Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MT0G03AP	SOT-223	0G03AP	2,500	5,000	35,000	13"reel

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Condition	Min	Typ	Max	Unit
--------	-----------	-----------	-----	-----	-----	------

Static Electrical Characteristics @ T_J = 25°C (unless otherwise stated)

BV _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =-250μA	-60	–	–	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-60V, V _{GS} =0V	–	–	-1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V, V _{DS} =0V	–	–	±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250μA	-1.0	-1.7	-2.5	V
R _{DS(on)}	Drain-Source On-State Resistance	V _{GS} =-10V, I _D =-3A	–	160	180	mΩ
		V _{GS} =-4.5V, I _D =-2A	–	200	250	mΩ

Dynamic Electrical Characteristics @ T_J = 25°C (unless otherwise stated)

C _{ISS}	Input Capacitance	V _{DS} =-30V, V _{GS} =0V, f=1MHz	–	430	–	pF
C _{OSS}	Output Capacitance		–	33	–	pF
C _{RSS}	Reverse Transfer Capacitance		–	22	–	pF







Switching Characteristics

Q _g	Total Gate Charge	V _{DD} =-30V, I _D =-2A, V _{GS} =-10V	–	8.5	–	nC
Q _{gs}	Gate Source Charge		–	2.1	–	nC
Q _{gd}	Gate Drain Charge		–	1.6	–	nC
t _{d(on)}	Turn-on Delay Time	V _{DD} =-30V, I _D =-1A, V _{GS} =-10V, R _G =6Ω	–	5.3	–	nS
t _r	Turn-on Rise Time		–	20	–	nS
t _{d(off)}	Turn-Off Delay Time		–	33	–	nS
t _f	Turn-Off Fall Time		–	10	–	nS



Source- Drain Diode Characteristics

V _{SD}	Forward on voltage	T _J =25°C, I _S =-2A	–	–	-1.2	V
-----------------	--------------------	---	---	---	------	---

Typical Operating Characteristics



SOT-223 Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	--	1.800	--	0.071
A1	0.020	0.100	0.001	0.004
A2	1.500	1.700	0.059	0.067
b	0.660	0.840	0.026	0.033
b1	2.900	3.100	0.114	0.122
c	0.230	0.350	0.009	0.014
D	6.300	6.700	0.248	0.264
E	3.300	3.700	0.130	0.146
E1	6.700	7.300	0.264	0.287
e	2.300(BSC)		0.091(BSC)	
L	0.750	--	0.030	--
θ	0°	10°	0°	10°