


Features

- Trench Power LV MOSFET technology
- High Power and Current handling capability
- Low Gate Charge

Application

- PWM applications
- Power management
- Load switch



MU0D88A : Device code
 XXXX : Code


Marking and pin assignment

Product Summary

V_{DS}	$R_{DS(ON)}$ TYP	I_D
30V	4.0mΩ@10V	88A
	7.4mΩ@4.5V	



TO-252 top view



Schematic diagram



Halogen-Free

Absolute Maximum Ratings (TA=25°C unless otherwise noted)

Symbol	Parameter	Rating	Unit
--------	-----------	--------	------

Common Ratings (TC=25°C Unless Otherwise Noted)

V _{DS}	Drain-Source Breakdown Voltage		30	V
V _{GS}	Gate-Source Voltage		±20	V
T _J	Maximum Junction Temperature		150	°C
T _{STG}	Storage Temperature Range		-55 to 150	°C
I _S	Diode Continuous Forward Current	Tc=25°C	88	A

Mounted on Large Heat Sink

I_{DM}	Pulse Drain Current Tested	$T_c=25^\circ\text{C}$	300	A
I_D	Continuous Drain Current	$T_c=25^\circ\text{C}$	88	A
P_D	Maximum Power Dissipation	$T_c=25^\circ\text{C}$	54	W
$R_{\theta JA}$	Thermal Resistance Junction-to-Ambient		89	°C/W

Ordering Information (Example)

Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MU0D88A	TO-252	MU0D88A	2,500	5,000	35,000	13"reel

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Condition	Min	Typ	Max	Unit
--------	-----------	-----------	-----	-----	-----	------

Static Electrical Characteristics @ T_J = 25°C (unless otherwise stated)

BV _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	28	30	--	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =25V, V _{GS} =0V	--	--	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V, V _{DS} =0V	--	--	±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	1.0	1.5	2.5	V
R _{DS(on)}	Drain-Source On-State Resistance	V _{GS} =10V, I _D =30A	--	4.0	4.8	mΩ
		V _{GS} =4.5V, I _D =10A	--	7.4	10	mΩ

Dynamic Electrical Characteristics @ T_J = 25°C (unless otherwise stated)

C _{ISS}	Input Capacitance	V _{DS} =12.5V, V _{GS} =0V, f=1MHz	--	1050	--	pF
C _{OSS}	Output Capacitance		--	220	--	pF
C _{RSS}	Reverse Transfer Capacitance		--	190	--	pF







Switching Characteristics

Q _g	Total Gate Charge	V _{DS} =12.5V, I _D =30A, V _{GS} =10V	--	33	--	nC
Q _{gs}	Gate Source Charge		--	7	--	nC
Q _{gd}	Gate Drain Charge		--	11	--	nC
t _{d(on)}	Turn-on Delay Time	V _{DD} =12.5V, I _D =30A, V _{GS} =10V, R _G =2.5Ω	--	6	--	nS
t _r	Turn-on Rise Time		--	20.5	--	nS
t _{d(off)}	Turn-Off Delay Time		--	19	--	nS
t _f	Turn-Off Fall Time		--	9	--	nS


Source- Drain Diode Characteristics

V _{SD}	Forward on voltage	T _J =25°C, I _S =30A	--	--	1.2	V
-----------------	--------------------	---	----	----	-----	---

Typical Operating Characteristics



TO-252 Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
b	0.635	0.770	0.025	0.030
c	0.450	0.580	0.018	0.023
D	6.500	6.700	0.256	0.264
D1	5.100	5.460	0.201	0.215
D2	4.830 REF.		0.190 REF.	
E	6.000	6.200	0.236	0.244
e	2.186	2.386	0.086	0.094
L	9.712	10.312	0.386	0.406
L1	2.900 REF.		0.114 REF.	
L2	1.400	1.700	0.055	0.067
L3	1.600 REF.		0.063 REF.	
L4	0.600	1.000	0.024	0.039
Φ	1.100	1.300	0.043	0.051
θ	0°	8°	0°	8°
h	0.000	0.300	0.000	0.012
V	5.250 REF.		0.207 REF.	